


Ø6mm / M6 Suspensions

- See pages 222-223 for Micro Series framing components.
- See pages 412–416 for Mini Vacuum Cups and M3 Fittings.
- See page 486 for Micro Series Sprue Grippers.
- For rotationally symmetrical vacuum cups. (Do not use with Oval cups)
- Two options for fitting placement. It can either be fed through the side port (plugged initially) or it can pass through the vacuum channel which extends through the suspension body.
- It is recommended to use soft tubing and barb fittings on micro sized suspensions to prevent suspension binding.



Micro Series Clampable Suspension

Quick#	Part#	>ASS< #	Туре	Price	Wt.
3790	GAF6-U-10	1-355-01-00	Rotate	\$23.63	6g



Micro Series Threaded Suspension

Quick#	Part#	>ASS< #	Туре	Price	Wt.
3791	GAF6-M-10	1-355-02-00	Rotate	\$24.68	9g

Self-Retracting Suspension

- The VHE pulls the vacuum cup in as soon as the vacuum cup seals and vacuum is engaged.
- The internal spring extends the arm as soon as vacuum is disengaged.
- G1/8" air ports.
- Extendable reach with M17x1 thread and VLR Extension tubes.
- Anodized aluminum Ø20mm clampable body.
- · Dimensional drawing can be found online.



Ø20mm Clampable Self-Retracting Suspension

Quick#	Part#	>ASS< #	Stroke	Style	Price	Wt.
3948	VHE-20	1-775-00-00	20mm	Rotate	\$174.30	48g
3953	VHE-20-VG	1-775-00-00-1	20mm	Non-Rotate	\$174.30	48g