

Gimatic T-Slot & Dovetail Sensors


T-Slot Sensors

Part#	Quick#	Price	Type	Signal	Connection	Power Supply	Max. Switching Frequency	Voltage Drop	Operating Temperature	IEC Rating	Cable
SL4N225G	792	\$26.14	3-wire Magneto-resistive	PNP	2.5m lead	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SL4M225G	793	\$26.14	3-wire Magneto-resistive	NPN	2.5m lead	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SL3N203G	6274	\$29.96	3-wire Magneto-resistive	PNP	.3m lead & M8	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SL3M203G	6456	\$29.96	3-wire Magneto-resistive	NPN	.3m lead & M8	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SC3N203G	6455	\$33.29	3-wire Magneto-resistive	PNP	.3m lead & M8	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SC3M203-G	6457	\$33.29	3-wire Magneto-resistive	NPN	.3m lead & M8	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SC4N225G	6273	\$29.13	3-wire Magneto-resistive	PNP	2.5m lead	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath
SC4M225-G	1796	\$29.13	3-wire Magneto-resistive	NPN	2.5m lead	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	PUR Sheath


Dovetail-Slot Sensors

Part#	Quick#	Price	Type	Signal	Connection	Power Supply	Max. Switching Frequency	Voltage Drop	Operating Temperature	IEC Rating	Cable
CB3N2-G	6126	\$22.00	3-wire Magneto-resistive	PNP	M8 Connector*	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	6591
CB3M2-G	1794	\$22.00	3-wire Magneto-resistive	NPN	M8 Connector*	6-30V dc	200 KHz	1V dc	-10 to +70°C	IP 67	6591

(*) Purchase extension cable #6591 separate for these sensors. Visit website for more information.



T-Slot dimensional drawing



Dovetail dimensional drawing

For Gimatic SP gripper #6281 use Gimatic SC & SL sensors.



SC...

SL...

CB...

3-Wire Configuration:

